

# SM/MSM BackLoad

The world standard for  
backload configuration



Proven Global Solution

Flexible Configuration for  
Multiple OEM Applications

Lowest Cost of Ownership

bill validator



CRANE PAYMENT INNOVATIONS

CPI Headquarters  
3222 Phoenixville Pike, Suite 200  
Malvern, PA 19355 USA  
Office: +1 610 430 2700 E-mail: sales@CranePI.com  
For additional office locations or product information  
please visit [www.CranePI.com](http://www.CranePI.com)



# The world standard for backload configuration

## SM/MSM BackLoad



### Features

- Superior acceptance and security: first pass acceptance 96+%
- Advanced auto-calibrating optical, inductive and dielectric sensors optimize validation rates
- Anti-stringing protection
- Secure lockable-removable cassettes available in multiple capacities
- Four-way bill insertion
- Complete transport cycle at only 1.7 seconds
- High impact resistant cash vault
- Durable, metal chassis

### Convenience for You and Your Customers

- Installs in an up or down stacking configuration
- Beltless transport system lowers maintenance costs
- Tool-free, one-step, easy service access
- Remote-upgradable using CCNet protocol
- Quick and easy diagnostics via LED indicator



Smart-Stick updates



Choice of bezels

SM/MSM BackLoad Validator	
Bill Width Validated	67 or 71 mm wide (fixed-width) 62 - 78 mm wide (multi-width)
Complete Transport Cycle	1.7 sec (fixed-width) 2.5 sec (multi-width)
Bill Insertion	Four-way
Validation Rate	96% or higher
Escrow	One bill
Sensors	Auto-calibrating multi-color optical, dielectric, inductive, and
Security Sensors	Cross-channel (anti-stringing) and dual-entry barcode reader
Bezel Options	Standard, Running lights, coin/vandal-resistant metal bezel
Interfaces Supported	12V: pulse, serial or bi-directional (with TTL or RS232)
Protocols	24V: MDB, single price, CCNet, CashCode serial, MDB, pulse, and most other industry protocols
Firmware Updates	BlueChip™ Smart-Stick memory or downloadable
Operating Voltage	2V DC: 2.0 A; 24V AC or 15-42.5 V DC: 1.0 A / Sleep mode version 10µA vs 100 – 200 mA in normal operation
Operating Temperature	12V: 0° C to 50° C; 24V: -18° C to 60° C
Dimensions (W x H x D)	104 x 266 x 87mm
Weight	< 1.2 kg
Cassette Sizes Available	400, 600 or 1500 (fixed width); 300 (horizontal); 300, 500, 1000 (multi-width)
Cassette Options	Standard: up to two custom locks High-security Gaming: up to three custom locks
Manufactured in	Canada