

IM15

COMPACT

Contactless Unattended



EV Charger



Transportation



Self-Service



UNATTENDED



Powered by
Prolin



PCI 6
SRED



Advanced
Connectivity



2 MP
Front



















IP65
IK09

www.paxitalia.com

 MAXSTORE

SPECIFICATIONS

	Operating System	Prolin
	Processor	Cortex A5
	Memory	128MB Flash + 256MB DDR RAM 512MB Flash + 512MB DDR RAM (optional)
	Card Readers	Contactless
	Code Reader	Reads 1D & 2D Codes
	Display	3.5" TFT LCD 480 x 320 Touch Screen Support PIN on Glass
	Comms Configurations	LAN Wi-Fi® 5 & Bluetooth 5.0 ® (optional) 4G (optional)
	SAM	2 SAM
	Keys / Buttons	1 x Reset key
	Audio	1 Speaker
	Ports	1 x USB Host 1 x USB Device 1 x LAN 1 x RS232 1 x Digital I/O 1 x MDB Slave
	Physical	108 x 75 x 43mm Cutout: 73 x 61mm
	Accessories	Mounting Fixture External 4G Antenna (optional)
	Power Supply	12V - 48V DC via MDB or RS232 or Digital I/O
	Environmental	-20°C ~ 70°C (-4°F ~ 158°F) Operating Temperature -30°C ~ 70°C (-22°F ~ 158°F) Storage Temperature 5% ~ 95% Relative Humidity, Non-Condensing
	Certifications	PCI PTS 6.x, SRED EMV Contactless L1 qPBOC L1 qUICS L2 Mastercard payPass L2 Visa payWave L2 American Express ExpressPay L2 Discover D-PAS L2 Interac_Flash L2 J/Speedy L2 Mastercard TQM FCC IC UL RoHS CE CSEC UKCC IP65 IK09

